

UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.
5-009US-FF

Total Pages in this Submission

TO THE ASSISTANT COMMISSIONER FOR PATENTS

Box Patent Application
Washington, D.C. 20231

Transmitted herewith for filing under 35 U.S.C. 111(a) and 37 C.F.R. 1.53(b) is a new utility patent application for an invention entitled:

IMAGE SERVER AND METHOD OF CONTROLLING SAME

10041 U.S. PTO
09/66770
09/22/00

and invented by:

Yoshiki Kawaoka, Norihisa Haneda, Hiroshi Suganuma and Hiroyuki Yoshinaga

If a **CONTINUATION APPLICATION**, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: _____

Which is a:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: _____

Which is a:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: _____

Enclosed are: *

Application Elements

1. ☒ Filing fee as calculated and transmitted as described below
2. ☒ Specification having 54 pages and including the following:
 - a. ☒ Descriptive Title of the Invention
 - b. ☐ Cross References to Related Applications (if applicable)
 - c. ☐ Statement Regarding Federally-sponsored Research/Development (if applicable)
 - d. ☐ Reference to Microfiche Appendix (if applicable)
 - e. ☒ Background of the Invention
 - f. ☒ Brief Summary of the Invention
 - g. ☒ Brief Description of the Drawings (if drawings filed)
 - h. ☒ Detailed Description
 - i. ☒ Claim(s) as Classified Below
 - j. ☒ Abstract of the Disclosure

UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.
5-009US-FF

Total Pages in this Submission

Application Elements (Continued)

3. ☒ Drawing(s) *(when necessary as prescribed by 35 USC 113)*
- a. ☒ Formal Number of Sheets 21 (Figs. 1-22)
- b. ☐ Informal Number of Sheets _____
4. ☒ Oath or Declaration
- a. ☒ Newly executed *(original or copy)* ☐ Unexecuted
- b. ☐ Copy from a prior application (37 CFR 1.63(d)) *(for continuation/divisional application only)*
- c. ☒ With Power of Attorney ☐ Without Power of Attorney
- d. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application,
see 37 C.F.R. 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation By Reference *(usable if Box 4b is checked)*
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied
under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby
incorporated by reference therein.
6. ☐ Computer Program in Microfiche *(Appendix)*
7. ☐ Nucleotide and/or Amino Acid Sequence Submission *(if applicable, all must be included)*
- a. ☐ Paper Copy
- b. ☐ Computer Readable Copy *(identical to computer copy)*
- c. ☐ Statement Verifying Identical Paper and Computer Readable Copy

Accompanying Application Parts

8. ☒ Assignment Papers *(cover sheet & document(s))*
9. ☐ 37 CFR 3.73(B) Statement *(when there is an assignee)*
10. ☐ English Translation Document *(if applicable)*
11. ☐ Information Disclosure Statement/PTO-1449 ☐ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Acknowledgment postcard
14. ☐ Certificate of Mailing
- ☐ First Class ☐ Express Mail *(Specify Label No.):* _____

UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.
5-009US-FF

Total Pages in this Submission

Accompanying Application Parts (Continued)

15. ☒ Certified Copy of Priority Document(s) (if foreign priority is claimed)

16. ☐ Additional Enclosures (please identify below):


10041 U.S. PTO
09/667701
09/22/00

Fee Calculation and Transmittal

CLAIMS AS FILED

For	#Filed	#Allowed	#Extra	Rate	Fee
Total Claims	20	- 20 =	0	x \$18.00	\$0.00
Indep. Claims	14	- 3 =	11	x \$78.00	\$858.00
Multiple Dependent Claims (check if applicable) <input type="checkbox"/>					\$0.00
BASIC FEE					\$690.00
OTHER FEE (specify purpose) Assignment Recordation					\$40.00
TOTAL FILING FEE					\$1,588.00

- ☒ A check in the amount of **\$1,588.00** to cover the filing fee is enclosed.
- ☒ The Commissioner is hereby authorized to charge and credit Deposit Account No. **50-0481** as described below. A duplicate copy of this sheet is enclosed.
- ☐ Charge the amount of _____ as filing fee.
- ☒ Credit any overpayment.
- ☒ Charge any additional filing fees required under 37 C.F.R. 1.16 and 1.17.
- ☐ Charge the issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance, pursuant to 37 C.F.R. 1.311(b).


Signature

Dated: September 22, 2000

Sean M. McGinn, Esq.
Reg. No. 34,386

CC:

Customer No.: 21254

MCGINN & GIBB, P.C.
A PROFESSIONAL LIMITED LIABILITY COMPANY
PATENTS, TRADEMARKS, COPYRIGHTS, AND INTELLECTUAL PROPERTY LAW
1701 CLARENDON BOULEVARD, SUITE 100
ARLINGTON, VIRGINIA 22209
TELEPHONE (703) 294-6699
FACSIMILE (703) 294-6696

**APPLICATION
FOR
UNITED STATES
LETTERS PATENT**

APPLICANT: Yoshiki Kawaoka, Norihisa Haneda, Hiroshi
Suganuma and Hiroyuki Yoshinaga

FOR: IMAGE SERVER AND METHOD OF
CONTROLLING SAME

DOCKET NO.: 5-009US-FF

002250" T04.9950

SPECIFICATION

TITLE OF THE INVENTION

IMAGE SERVER AND METHOD OF CONTROLLING SAME

BACKGROUND OF THE INVENTION

5 Field of the Invention

This invention relates to an image server and a method of controlling the same, a client terminal and a method of controlling the same, an image printing system and method, a data installing apparatus and a method of
10 controlling the same, an image data output apparatus and method, and a printing management apparatus and method.

Description of the Related Art

With the growth of the Internet and the widespread use of personal computers, it has become possible for
15 individuals to send and receive data containing a large quantity of data, such as image data. A large quantity of image data can be stored in a server in advance, the image data can be downloaded by accessing the server and images represented by the image data can be printed
20 using a printer.

It is a general rule that an individual who takes or creates a picture has the copyright to the picture. Copyright-free pictures (pictures for which the copyright has been abandoned) are the exception rather
25 than the rule.

Accordingly, it is important to prevent persons who are not duly authorized users from making unlawful use of image data, as by inhibiting printing of images. To

002250-102950

achieve this, copyright management of images is vital.

SUMMARY OF THE INVENTION

Accordingly, an object of the present invention is to arrange it so that an individual having the legal
5 privilege to an image can utilize the image.

Another object of the present invention is to manage the printing conditions of an image in a comparatively simple manner.

According to a first aspect of the present
10 invention, the foregoing objects are attained by providing an image server for outputting encrypted image data to at least one client terminal among a plurality thereof, comprising: a selection unit for selecting, from among the plurality of client terminals, a client
15 terminal to which image data is to be output; an encryption unit (encryption means) for encrypting the image data using an encryption key which corresponds to the client terminal that has been selected by the selection unit; and an encrypted image data output unit
20 for outputting image data that has been encrypted by the encryption unit.

The first aspect of the present invention provides also a method of controlling the above-described image server. Specifically, there is provided a method of
25 controlling an image server for outputting encrypted image data to at least one client terminal among a plurality thereof, the method comprising the steps of: selecting, from among the plurality of client terminals,

002260-09200

a client terminal to which image data is to be output;
encrypting the image data using an encryption key which
corresponds to the client terminal that has been
selected; and outputting image data that has been
5 encrypted.

In accordance with the first aspect of the present
invention, an encryption key used for encryption is
decided for each of the plurality of client terminals.
(For example, an encryption key may be decided for each
10 group of a plurality of client terminals or a different
encryption key may be decided for each client terminal.)
At least one client terminal is selected from among the
plurality thereof. Image data is encrypted using the
encryption key corresponding to the selected client
15 terminal, and the encrypted image data is output to the
selected client terminal.

Thus, in accordance with the first aspect of the
present invention, an encryption key is decided for each
client terminal and encryption is performed using the
20 encryption key that corresponds to the selected client
terminal. By deciding a decryption key corresponding to
an encryption key for every client terminal, decryption
can be carried out using the decryption key that has
been decided. Decryption can be performed at one client
25 terminal among a plurality thereof, thereby making it
possible to prevent decryption at the other client
terminals. Thus, a user or operator of an unauthorized
client terminal will not be able to decrypt image data

002260-102260

that has been encrypted.

Image data may be output by transmitting the image data, or an arrangement may be adopted in which image data is output by being recorded on a portable recording
5 medium (a floppy disk, CD-ROM, memory card, etc.).

Image data may include high-resolution image data for printing and display image data having a resolution lower than that of the high-resolution image data for printing.

10 In this case, the high-resolution image data for printing would be encrypted.

Since the display image data need not necessarily be encrypted, it can be displayed without decryption. Because the display image data has a resolution lower
15 than that of the image data for printing, damage ascribable to any unlawful use will be minimal.

A second aspect of the present invention relates to the decrypting of image data that has been encrypted by the first aspect of the present invention. A client
20 terminal in accordance with the second aspect of the present invention comprises an input unit for inputting image data that has been encrypted using an encryption key which corresponds to this client terminal; a decryption unit (decryption means) for decrypting
25 encrypted image data, which has been input by the input unit, using the corresponding decryption key; and an output unit for outputting image data that has been decrypted by the decryption unit.

002260-1029950

The second aspect of the present invention provides also a control method suited to the above-described client terminal. Specifically, the method comprises the steps of: inputting image data that has been encrypted
5 using an encryption key which corresponds to the client terminal; decrypting input encrypted image data using the corresponding decryption key; and outputting image data that has been decrypted.

In accordance with the second aspect of the present
10 invention, image data that has been encrypted using an encryption key corresponding to a client terminal is entered. The entered encrypted image data is decrypted by the corresponding decryption key and then output.

Thus, decryption can be performed using a
15 decryption key even if the encryption key differs for each client terminal.

Input of encrypted image data may be performed by receiving image data that has been transmitted or by reading encrypted image data that has been recorded on a
20 portable recording medium.

Further, output of decrypted image data may be performed by transmitting decrypted image data or by writing decrypted image data to a portable recording medium.

25 An image printing system according to a third aspect of the present invention comprises: an image selection unit for selecting at least one image from among a plurality thereof; a print command unit for

002260-092200

applying a command to print the image that has been selected by the image selection unit; and a printing unit, which is responsive to a print command applied by the print command unit, for printing, on the same
5 visible recording medium, the image that has been selected by the image selection unit and information relating to a copyright holder of the selected image.

The third aspect of the present invention provides also a method suited to the above-described system.

10 Specifically, the method comprises the steps of:
selecting at least one image from among a plurality thereof; receiving a command to print the image that has been selected; in response to a print command applied by the print command unit, printing, on the same visible
15 recording medium, the image that has been selected and information relating to a copyright holder of the selected image.

In accordance with the third aspect of the present invention, one image is selected from among a plurality
20 thereof. When a command to print a selected image is applied, the selected image and information relating to the copyright holder of the image are printed on the same visible recording medium.

Since an image and information relating to the
25 copyright holder of the image are recorded on the same visible recording medium, the copyright holder of the image can be ascertained merely by looking at the visible recording medium. Since the copyright holder of

002260 T01 092200

the image can be determined, unlawful use of the printed image can be prevented.

The information relating to the copyright holder may be the name of the copyright holder per se, an
5 indication to the effect that the image is not copyright free, or image indicating the source of the image.

Information relating to the copyright holder may be input by the operator or may be stored as data in the same image file that contains the image data
10 representing the image. The image data is read out of the file and the image represented by the image data is printed. Data representing the information relating to the copyright holder is read out of this file and the information relating to the copyright is recorded on the
15 visible recording medium on which the image has been recorded.

The visible recording medium refers to a medium such as paper or film on which an image is printed so that the image can be seen by the human eye.

20 Data in which the image data representing a plurality of images and information relating to the copyrights of these images are associated with each other may be entered. In this case a desired image would be selected from among the plurality of images
25 represented by the entered image data.

An image printing system according to a fourth aspect of the present invention comprises: a scanner for reading an image that has been recorded on a visible

002260-092200

002260 1079560

recording medium and outputting image data representing the read image; a determination unit (determination means) for determining whether an image that has been read by the scanner contains information relating to a copyright holder of the image; an image printing unit for printing an image, which has been read by the scanner, in accordance with a determination by the determination unit that the read image does not contain information relating to the copyright holder; and a printing controller (printing control means) for halting normal printing of the image by the image printing unit in accordance with a determination by the determination unit that the read image contains information relating to the copyright holder.

15 The fourth aspect of the present invention provides also a method suited to the above-described system. Specifically, the method comprises the steps of: reading an image that has been recorded on a visible recording medium and acquiring image data representing the read image; determining whether an image that has been read contains information relating to a copyright holder of the image; printing an image, which has been read, in accordance with a determination that the read image does not contain information relating to the copyright holder; and halting normal printing of the image in accordance with a determination that the read image contains information relating to the copyright holder.

002260" 10/29/95

In accordance with the fourth aspect of the present invention, an image that has been recorded on the visible recording medium is read. It is determined whether the read image contains information relating to the copyright holder of this image. If it is determined that the read image does not contain information relating to the copyright holder of the image, then the read image is printed. If it is determined that the read image contains information relating to the copyright holder of the image, normal printing of this read image is halted.

If an image contains information relating to the copyright holder, then this image is considered not to be copyright free. Accordingly, there is the danger that the image may be decrypted unlawfully by a person other than a duly authorized user. In accordance with the fourth aspect of the present invention, normal printing is halted if an image contains information relating to a copyright holder. As a result, unlawful decryption of an image by a person other than a duly authorized user can be prevented.

Normal printing means printing such that the image obtained by printing is recognized as being substantially identical with the original image. The halting of normal printing means stopping the printing of an image per se, performing printing such that the printed image will not be recognized as being the original image, e.g., printing a warning statement,

which indicates that the copy is unlawful, in a form superimposed on the original image, or printing only a portion of the original image. In any case, it will suffice if the image obtained by printing is one that
5 will not be recognized as being identical with the original image.

In accordance with a fifth aspect of the present invention, there is provided a data installing apparatus for reading data from a first portable recording medium
10 on which the data has been recorded and installing the image data that has been read, wherein a unique first password has been stored in an image printing unit and the apparatus comprises: a password reading unit for reading a second password from a second portable
15 recording medium on which the second password has been rewritably recorded; a password determination unit (password determination means) for determining whether the first password and the second password, which has been read by the password reading unit, match; a first
20 installation unit (first installation means) for executing the installation in response to a determination by the password determination unit that the first and second passwords match; and an installation inhibiting unit (installation inhibiting
25 means) for inhibiting the installation in response to a determination by the password determination unit that the first and second passwords do not match.

The fifth aspect of the present invention provides

002260-092200

also a method suited to the above-described data
installation apparatus. Specifically, there is provided
a data installation method in a data installing
apparatus for reading data from a first portable
5 recording medium on which the data has been recorded and
installing the image data that has been read, wherein a
unique first password has been stored in the data
installation apparatus and the method comprises the
steps of: reading a second password from a second
10 portable recording medium on which the second password
has been rewritably recorded; determining whether the
first password and the second password, which has been
read, match; executing the installation in response to a
determination that the first and second passwords match;
15 and inhibiting the installation in response to a
determination that the first and second passwords do not
match.

In accordance with the fifth aspect of the present
invention, data (image data, programs, etc.) has been
20 recorded on the first portable recording medium.
Further, the unique first password has been stored in
the data installing apparatus (e.g., an image printing
apparatus). Furthermore, the second password has been
rewritably stored on the second portable recording
25 medium.

Before data that has been stored on the first
portable recording medium is installed in the data
installing apparatus, the second password is read from

002250-092200

the second portable recording medium and then it is determined whether the read second password matches the first password of the data installing apparatus.

5 If the two passwords match, then it is recognized that the first portable recording medium is for the data installing apparatus having the matching first password. Image data that has been stored on the first portable recording medium can be installed in the data installing apparatus. If the two passwords do not match, then it
10 is construed that the first portable recording medium is not for the data installing apparatus having the first password and that an attempt is being made to perform installation by utilizing it for another data installing apparatus. Image data that has been stored on the first
15 portable recording medium is inhibited from being installed in the data installing apparatus.

In accordance with the fifth aspect of the present invention, data that can be installed in the data installing apparatus is data that has been recorded on
20 the first portable recording medium for this data installing apparatus. Data that has been recorded on the first portable recording medium determined to be for prescribed data installing apparatus is inhibited from being installed in the other data installing apparatus.
25 Thus, data can be installed only by a duly authorized person (i.e., in a legitimate data installing apparatus). This makes it possible to prevent unlawful installation.

002260-102950

002260" T049950

Data indicating the number of installations may be recorded on the second portable recording medium. In this case the data indicating the number of installations recorded on the second portable recording medium is read and, when the number of installations indicated by this read data is zero, password determination is halted. The installation is executed in response to the halting of password determination and the number of installations indicated by the data that has been recorded on the second portable recording medium is incremented in response to execution of installation.

When the number of installations is zero, the first installation takes place. When installation is performed the first time, this is construed as being a lawful installation and execution of the installation is allowed.

The second password may be the initial data prevailing before installation. In this case installation is inhibited in response to a number of installations that is zero and, moreover, a second password that is not initial data.

When the number of installations is zero, the second password should be initial data. When the second password is not initial data regardless of the fact that the number of installations is zero, this means that a malfunction has occurred. Installation is inhibited as a result.

002260"FDZ9960

In accordance with a sixth aspect of the present invention, there is provided an image data output apparatus for outputting image data corresponding to a plurality of image printing units which print images represented by image data, comprising: a designation unit for designating an output destination of applied image data from among the plurality of image printing units; a format conversion unit (format conversion means) for converting a format of the applied image data so as to obtain a format conforming to the image printing unit that has been designated by the designation unit; and an image data output unit for outputting the image data, the format whereof has been converted by the format conversion unit, to the image printing unit that has been designated by the designation unit.

The sixth aspect of the present invention provides also a method suited to the above-described image data output apparatus. Specifically, there is provided an image data output method in an image data output apparatus for outputting image data corresponding to a plurality of image printing units which print images represented by image data, comprising the steps of: designating an output destination of applied image data from among the plurality of image printing units; converting a format of the applied image data so as to obtain a format conforming to the image printing unit that has been designated; and outputting the image data,

the format whereof has been converted, to the image printing unit that has been designated.

In accordance with the sixth aspect of the present invention, image data is applied. An output destination
5 of the applied image data is designated from among a plurality of image printing units and the format of the applied image data is converted so as to become a format conforming to the designated image printing unit. (For
10 example, the size of the image is adjusted to the size of the image printed by the image printing unit.) The image data having the format obtained by the conversion is output to the designated image printing unit.

Thus, image data undergoes a format conversion so as to be suited to the designated image printing unit
15 and then is output to this printing unit. As a result, a format conversion at the image printing unit is unnecessary. This makes it possible to use an image printing unit having a simple construction.

When the image printing unit and the image data
20 output apparatus are capable of sending and receiving data, image data whose format has been converted can be output by being transmitted from the image data output apparatus to the image printing unit. When the image printing unit and image data output apparatus cannot
25 send and receive data, image data that has been output from the image data output apparatus is recorded on a portable recording medium. The portable recording medium on which the image data has been recorded is

002250"TDZ9350

carried to the corresponding image printing unit, where the image data that has been recorded on the portable recording medium is read.

5 An image file containing the image data and data indicating the output destination of this image data may be entered. In this case the output destination of the image data would be designated by the data indicating the output destination that is contained in the entered image file.

10 In accordance with a seventh aspect of the present invention, there is provided a printing management apparatus for managing printing conditions in a plurality of image printing units which print images represented by image data, wherein data representing
15 printing history is output from the image printing units and the apparatus comprises: a reading unit for reading data representing the printing history output from the image printing units, and a format conversion unit (format conversion means) for converting the data
20 representing the printing history read by the reading unit to data having a predetermined format.

The seventh aspect of the present invention provides also a method suited to the above-described printing management apparatus. Specifically, there is
25 provided a printing management method for managing printing conditions in a plurality of image printing units which print images represented by image data, wherein data representing printing history is output

002260-1029950

from the image printing units and the method comprises the steps of: reading data representing the printing history output from the image printing units, and converting the data representing the printing history
5 read to data having a predetermined format.

In accordance with the seventh aspect of the present invention, data representing printing history is output from the image printing units and the data that has been output is read. The read data representing the
10 printing history is converted to data having a predetermined format.

In accordance with the seventh aspect of the present invention, data representing printing history is converted to data having a predetermined format. Since
15 the data representing the printing history can be unified in a predetermined format, management is comparatively easy to perform. Editing of the data representing the printing history also comparatively simple to carry out.

20 The format-converted data representing the printing history may be aggregated for each of the plurality of image printing units.

Other features and advantages of the present invention will be apparent from the following
25 description taken in conjunction with the accompanying drawings, in which like reference characters designate the same or similar parts throughout the figures thereof.

002250 TO 2250

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram illustrating the overall configuration of an image communication system according to a preferred embodiment of the present invention;

5 Fig. 2 is a flowchart illustrating the processing of the overall operation of the image communication system;

Fig. 3 is a block diagram illustrating the electrical construction of an image recording server;

10 Fig. 4 is a table illustrating the relationship between client terminals and encryption keys used when applying image files to these client terminals;

Fig. 5 is a block diagram illustrating the electrical construction of a distributing server;

15 Figs. 6 and 7 are block diagrams illustrating the electrical constructions of online and offline client terminals, respectively;

Fig. 8 illustrates the organization of image files;

20 Fig. 9 is a flowchart illustrating processing executed by the image registration server;

Figs. 10a and 10b illustrate the content of an attribute-information recording area and image-data recording area included in an image file;

25 Fig. 11 illustrates the content of the attribute-information recording area and image-data recording area included in an image file;

Fig. 12 is a flowchart illustrating processing executed by the distributing server;

002250 10/29/95

Fig. 13 is a flowchart illustrating printing processing at a client terminal;

Fig. 14 illustrates an example of an image printed at the client terminal;

5 Fig. 15 is a flowchart illustrating processing for preventing reprinting;

Fig. 16 illustrates number of installations and an installation key before and after installation of image data;

10 Fig. 17 is a flowchart illustrating processing for installing image data;

Fig. 18 illustrates an example of log data transmitted from an online client terminal;

15 Fig. 19 illustrates an example of log data written to a floppy disk at the online client terminal;

Fig. 20 is a flowchart illustrating processing for log aggregation;

Fig. 21 illustrates an example of unified-format data; and

20 Fig. 22 illustrates an example of aggregate log data.

DESCRIPTION OF THE PREFERRED EMBODIMENT

A preferred embodiment of the present invention will now be described with reference to the drawings.

25 Fig. 1 is a block diagram illustrating the general configuration of an image communication system, and Fig. 2 is a flowchart illustrating an overview of the operation of the image communication system.

002260" TO 229350

An image communication system obtains approval to use an image from an individual (referred to as the "image provider"), such as a baseball player, soccer player, singer or actor, who possesses the copyright to the image, and applies the image to a client terminal. The image is printed out at the client terminal and the printed image is delivered to the user.

The image communication system includes an image registration server 1, an image providing server 2, a distributing server 3, an operations server 4 and a billing server 6. These servers are connected by a network so as to be capable of communicating data with one another.

Online client terminals 5A, 5B capable of communicating with the operations server 4 are included in the image communication system. Furthermore, offline client terminals 5F, 5G, which input/output image data via a portable recording medium such as a memory card, CD-ROM (compact disc read-only memory) or FD (floppy disk), are included in the image communication system. The online client terminals 5A, 5B and offline client terminals 5F, 5G are installed at game centers, record stores, amusement parks and the like. It goes without saying that although the two online client terminals 5A, 5B and two offline client terminals 5F, 5G are illustrated in Fig. 1, a greater number of these terminals may be provided.

First, an image is supplied by the image provider.

002260-1049950

5

10

20

25

Image data contained in an image file is decrypted
5 at the client terminals 5A, 5B, 5F, 5G. The image
represented by the decrypted image data is printed (step
18). The printed image is delivered to the user of the
client terminal in exchange for a fee. A log to the
effect that the image has been printed also is generated
10 at the client terminal.

Log data input to the operations server 4 is transmitted to the billing server 6 (step 20). On the basis of the log data, the billing server 6 executes billing processing for each client terminal (step 21).
25 If necessary, a user fee is paid to the image provider in accordance with the totaled bill.

Further details of the image communication system will become apparent from the description that follows.

The overall operation of the image registration
server 1 is controlled by a CPU 31. The latter
functions also to encrypt image data based upon a
program.

The image registration server 1 includes a memory 33 for storing data temporarily and a hard-disk drive 34 for accessing a hard disk. The image registration server 1 further includes a modem 35 for communication via a network, and a keyboard/mouse control circuit 36 for controlling operation based upon an operating

In this embodiment, the size of an image to be
5 printed is specific to each client terminal.
Accordingly, processing to adjust the size of the image
data is executed by the image registration server 1 so
as to obtain a size suited to the printed image at each
client terminal. The image data, which has been
10 processed to adjust the size, is stored in the hard disk
corresponding to each client terminal.

In the communication system according to this
15 embodiment, image data input to the image registration
server 1 is encrypted thereby. As mentioned above, the
encrypted image data is transmitted to the servers 2, 3
and 4 and then is applied to the online client terminals
5A, 5B or offline client terminals 5F, 5G. Accordingly,
20 data indicative of encryption keys used in encryption
has been stored on the hard disk.

The encryption key differs for each client terminal. (The encryption key may differ for each group comprising a plurality of client terminals.) Data
25 indicative of decryption keys which correspond to the encryption keys has been stored in respective ones of the client terminals. Image data that has been encrypted using encryption keys corresponding to the

client terminals can be decrypted by the decryption keys corresponding to these encryption keys. This means that while encrypted image data can be decrypted at one client terminal, the encrypted image data cannot be
5 decrypted at the other client terminals. Of course, this does not prevent the use of a common key for all client terminals.

Fig. 5 is a block diagram illustrating the electrical construction of the distributing server 3.

10 The overall operation of the distributing server 3 is controlled by a CPU 51.

The distributing server 3 includes a hard disk 52, a hard-disk drive 53 for accessing the hard disk 52 and a memory 54 for storing data temporarily. The
15 distributing server 3 further includes a network interface 55 for communicating with the other servers 1, 2, 4 and 6, and a keyboard/mouse control circuit 56 for controlling the distributing server 3 based upon an operating command from a keyboard and mouse 57. A
20 display unit 59 controlled by a display control circuit 58 is connected to the distributing server 3. For each client terminal to which image data is to be applied, the image data is stored in a prescribed area of the hard disk 52 in distributing server 3.

25 Fig. 6 is a block diagram illustrating the electrical construction of the online client terminal 5A. The other online client terminal 5B is similarly constructed.

002260-1042950

The overall operation of the online client terminal 5A is controlled by a CPU 61. The latter functions also to execute processing for decrypting image data based upon a program.

5 A flatbed scanner 71, a printer 72 and a card reader 73 are connected to the client terminal 5A. An image that has been recorded on a visible recording medium is read by the flatbed scanner 71, and an image that has been recorded on a memory card is read by the
10 card reader 73. The image data that has been read is input to an image processing circuit 60 by an SCSI 62. Further, an image represented by image data is printed out by the printer 72.

002260" T0449960
15 The image processing circuit 60 of the terminal 5A includes a memory 63 for storing data temporarily and a hard-disk drive 64 for accessing a hard disk. The image processing circuit 60 includes a modem 65 for communicating with the operations server 4.

20 A display unit 68 controlled by a display control circuit 67 is connected to the image processing circuit 60 of the terminal 5A. A touch-sensitive panel 69 is formed on the screen of the display unit 68. A signal indicating that the touch-sensitive panel 69 has been touched is input to the image processing circuit 60 by a
25 control circuit 66 for the touch-sensitive panel 69.

Data indicative of the decryption key specific to the terminal 5A, a specific serial number (ABC0001) and a terminal ID have been stored on the hard disk of the

terminal 5A, as mentioned earlier.

Fig. 7 is a block diagram illustrating the electrical construction of the offline client terminal 5F. Circuits in Fig. 7 identical with those of the online client terminal 5A shown in Fig. 6 are designated by like reference characters and need not be described again.

The offline client terminal 5F differs from the online client terminal 5A in that it is devoid of the modem 65 and includes a CD-ROM drive 74 for reading data that has been written to a CD-ROM 76 and an FD drive 75 for writing data to a floppy disk 77.

Image data has been written in and stored on the CD-ROM 76 by the operations server 4, as mentioned earlier. As will be described later, the number of installations of image data and an installation key that have been written to the CD-ROM 76 are written to the floppy disk 77. Image data that has been written to the CD-ROM 76 is installed only in a prescribed offline client terminal using these items of data.

Fig. 8 illustrates the organization of image files registered at the image registration server 1.

As shown in Fig. 8, "LIST" and image files (where "0001", "0002", "0003", "0004" are the file names of the image files) are managed by "ROOT". The file names of the image files managed by this arrangement and data indicating the types of images (template image or complete image) represented by the image data contained

10

15

20

25

image type indicating whether an image is a complete image or template image, by way of example, image size and image format. The print information includes printable size, printing orientation and printable
5 media. The billing information includes the amount of money, due date and number of valid prints.

With regard to a template image, the attribute information includes template information and mask image information. The template information includes an ID
10 indicating the category of the template and, if the template image is a calendar image, the total number of pages of the calendar and the calendar number, etc. The mask image information includes data indicating the number of masks, mask size and mask position.

15 The color-space information is data indicating the optimum color space of the image.

By registering files in the image registration server 1, the image files are stored in accordance with the organization shown in Fig. 8.

20 Fig. 9 is a flowchart illustrating the processing (step 11 in Fig. 2) executed by the image registration server 1.

The operator of the image registration server 1 receives images from the image provider. A client
25 terminal to which an image from among these received images is to be distributed is selected by the keyboard and mouse 38 (step 80).

A check is performed to determine whether the image

002260-1029950

15

20

25

and mask image or the data representing the completed image, the image data representing the display image, the attribute information and the color-space information, which have been stored in the memory 33, and a prescribed image-file name is attached to this image file (step 86).

If the image data is converted, it is entered by the client terminal to which the image data is to be applied. The image data undergoes a size adjustment to obtain the image size printed by the client terminal (step 87). It goes without saying that the size of the image printed by the client terminal is applied to the image registration server 1 beforehand.

If the image data is subjected to a size adjustment, then the encryption key corresponding to the client terminal selected at step 80 is read out of the hard disk. For example, if the selected client terminal is the online client terminal 5A, then the key A is read out of the hard disk. Encryption of the image data that has been stored in the memory 33 is carried out through a prescribed method using the key that has been read out (step 88). It goes without saying this encryption is for application to a complete image and template image.

The generated image file is registered in accordance with the organization shown in Fig. 8 described above (step 89).

The image file thus registered is transmitted from the image registration server 1 to the image providing

002250-102250

Figs. 10a, 10b and Fig. 11 illustrate the data
5 structure of attribute information and image data in an
image file.

Before the image data undergoes a size conversion,
15 encrypted image data is stored in an image-data
recording area, as shown in Fig. 10a.

If the size of image data is converted at the image registration server 1 in the manner described above (the

processing of step 87 in Fig. 9), then, as shown in Fig. 10b, data indicating the size of the print image of the client terminal that is the print target (in Fig. 10b, the print target is the No. 1 online client terminal and
5 the print size is A4) is stored as the print size in the attribute-information recording area. Also stored are the X- and Y-direction sizes conforming to the print size.

Image data after the size conversion is encrypted
10 and stored in the image-data recording area.

Fig. 11 illustrates the manner in which the attribute information and image data have been stored after the size conversion, where the print target is the No. 2 online client terminal.

15 The No. 2 online client terminal prints an image of size A6. Data indicative of "A6", therefore, has been stored as the print size. Further, data indicating the X- and Y-direction sizes corresponding to the image of size A6 has been stored as well.

20 Thus, the size of image data is adjusted at the image registration server 1 so as to conform to the print size of the client terminal to which the image data is to be applied.

Fig. 12 is a flowchart illustrating processing (the
25 processing of step 15 in Fig. 2) executed by the distributing server 3.

The print target is read from the attribute information contained in the image file (step 91).

002260" FD49360

panel 69 by the user, the image to be printed is selected.

A decryption key that has been stored on the hard disk of the client terminal is read out. From the image data that has been stored in the memory 63, image data for printing corresponding to the display image selected by the user is decrypted using the decryption key that has been read out (step 101). Print-mark data indicating the copyright holder based upon the copyright information that has been stored in the image file is inserted into the decrypted image data (step 102).

The image data into which the print-mark data has been inserted is applied to the printer 72 so that the image represented by the image data is printed (step 103). The printed image is thus output (step 104).

As shown in Fig. 14, the image representing the image data appears in an image recording area 106 on an output print 105. A copyright-information recording area 107 is formed at the lower right of the print 105. Information regarding the copyright holder represented by the print-mark data appears in the copyright-information recording area 107. In the example depicted in Fig. 14, characters reading "Printed by JOHN SMITH" appear in the copyright-information recording area 107. Here "JOHN SMITH" indicates the image copyright holder. Since the image copyright holder can be ascertained at a glance, copyright infringement can be prevented.

Further, since a decryption key corresponding to

002259-10429550

the encryption key has been stored only in the terminal that is the print target, decryption can be carried out only at the terminal that is the print target and not at other terminals. This means that the encrypted image data can be decrypted only at the client terminal of an operator who has the rightful privilege to use the image. Since the encrypted image data cannot be decrypted at a client terminal of an operator who does not possess the rightful privilege to use the image, it is possible to prevent unlawful use of image data by the operator of the client terminal.

Fig. 15 is a flowchart illustrating processing (the processing of step 18 in Fig. 2) for preventing unlawful reprinting at a client terminal.

If an image is printed in the manner described above, there are instances where the image is read using a scanner and printed again. Fig. 15 illustrates processing for preventing such unlawful reprinting.

A visible recording medium is placed on the flatbed surface of the flatbed scanner 71 and the image that has been recorded on the visible recording medium is read (step 111). Next, processing for detecting a printing mark from the copyright-information recording area 107 of the read image is executed (step 112).

If the read image contains a printing mark ("YES" at step 113), a decision is rendered to the effect that this is unlawful printing and a warning to this effect is displayed on the display unit 68 (step 115).

Processing for printing the image represented by the image data read by the scanner 71 is suspended.

If the read image does not contain a printing mark ("NO" at step 113), then it is decided that this is not
5 unlawful printing. Accordingly, print processing is executed by the printer 72 (step 114).

Fig. 16 illustrates the manner in which data indicating number of installations and data indicating an installation key changes, this data being stored on a
10 floppy disk used when image data is installed in an offline client terminal.

Image data has been stored on the CD-ROM 76, as mentioned above. Further, data indicating number of installations and data indicating an installation key
15 has been stored on the floppy disk 77.

The number of installations indicates the number of times the image data, which has been stored on the CD-ROM, has been installed in the offline client terminal. The installation key is used to prevent unlawful
20 installation of image data that has been stored on the CD-ROM 76.

The CD-ROM 76 is inserted into the CD-ROM drive 74 of the offline client terminal in which the image data is to be installed. Further, the floppy disk 77 paired
25 with the CD-ROM 76 is inserted into the FD drive 75.

In the initial state (i.e., when image data stored on the corresponding CD-ROM 76 has not been installed even once), "0" is stored on the floppy disk 77 as the

002250" T049950

number of installations and "first time" is stored on the floppy disk 77 as the installation key. If the image data on the CD-ROM 76 is installed, the number of installations is incremented. In addition, the
5 installation key is rewritten to the serial number of the offline client terminal. For example, if the serial number of the offline client terminal is "ABC0001", the installation key is rewritten from "first time" to "ABC0001".

10 Only an offline client terminal in which the CD-ROM 76 and floppy disk 77 have first been inserted and in which the image data has been installed can have image data installed within it again subsequently.

Fig. 17 is a flowchart illustrating processing (the
15 processing of step 18 in Fig. 2) for when image data that has been stored on the CD-ROM drive 74 is installed in an offline client terminal.

The CD-ROM 76 is inserted by the operator of the offline client terminal into the CD-ROM drive 74 of the
20 offline client terminal in which image data is to be installed, and the floppy disk 77 corresponding to the CD-ROM 76 is inserted in the FD drive 75 by the operator.

The number of installations is read out of the
25 floppy disk 77 that has been inserted into the FD drive 75. It is determined whether the read number of installations is "0" (step 121). If the number of installations is "0" ("YES" at step 121), this indicates

002250" FD/29950

that installation of image data has not yet been carried out. In this case the installation key should be "first time". If the installation key is "first time" ("YES" at step 122), then this is confirmation of initial
5 installation. Accordingly, image data is read from the CD-ROM 76 that has been inserted in the CD-ROM drive 74 and the image data is installed on the hard disk (step 123).

If installation is finished, the number of
10 installations read from the floppy disk 77 is incremented. Data indicating the incremented number of installations is written to the floppy disk 77 by the FD drive 75. The installation key is rewritten from "first time" to the serial number "ABC0001" of the offline
15 client terminal into which the floppy disk 77 has been inserted (step 124).

If the installation key is not "first time" ("NO" at step 122) regardless of the fact that the number of installations read from the floppy disk 77 is "0" ("YES"
20 at step 121), it is considered that some malfunction has occurred. In this case the installation processing is suspended and the fact that some malfunction has occurred is displayed on the display screen of the display unit 68.

25 If the number of installations read out of the floppy disk 77 is not "0" ("NO" at step 121), this indicates that installation has already been carried out. Next, it is determined whether the installation

002260"FDZ9950

When the number of installations is not "0" and the installation key is "ABC0001", then it is judged that the operator is attempting to install the image data in an offline client terminal that is the same as the offline client terminal in which installation was performed initially. In this case it is judged that this is processing by a duly authorized person and re-installation of the image data that has been recorded on the CD-ROM 76 is executed (step 126). If installation is finished, the number of installations that has been stored on the floppy disk 77 is incremented (step 127).

Thus, re-installation of image data is possible
25 only at an offline client terminal in which image data
was installed initially. This makes it possible to
prevent the unlawful installation of image data in
another offline client terminal.

If an image is printed at a client terminal, a history of this printing is generated and data representing the printing history is stored in memory 63 as log data. The log data is supplied from the client
5 terminal to the operations server 4. If the client terminal is online, the log data is transmitted to the operations server 4. If the client terminal is offline, then the log data is written to a floppy disk. The floppy disk to which the log data has been written is
10 carried to the operations server 4 and is read by the operations server 4.

In any case, log data that has been applied to the operations server 4 is transmitted to the billing server 6. The latter executes processing to aggregate the log
15 data.

Fig. 18 illustrates an example of log data transmitted from an online client terminal.

Log data is signified by a label and contains the following data:

20 Terminal ID

 This is a unique ID for identifying a terminal.

 Image ID

 This is an ID specific to an image used in printing.

25 Service Time

 This indicates the date and time at which an image was printed.

 Paper Type

002260" 10/23/50

Number of Prints

5 Fig. 19 illustrates the structure of log data
stored on a floppy disk by an offline client terminal.

Terminal ID, image ID, service time, paper type and
10 number of prints are managed by "ROOT" and this data is
stored on the floppy disk.

Fig. 20 is a flowchart illustrating processing for aggregating log data, Fig. 21 illustrates unified-format data for converting log data to data having a unified format, and Fig. 22 illustrates log data the format of which has been unified by the unified-format data.

If the received log data does not have a format identical with the unified format, which has been

decided in advance ("NO" at step 132), then the format is converted to a predetermined format (step 133) using the unified format shown in Fig. 21. If the received log data does have a format identical with the unified
5 format, which has been decided in advance ("YES" at step 132), then the processing of step 133 is skipped.

If the format is unified, then the log data is aggregated, as shown in Fig. 22, by the billing server 6 (step 134). The aggregated log data is then furnished
10 to the image provider.

It goes without saying that the billing server 6 also has a structure almost the same as that of the image registration server 1 and that the log-data aggregation processing is executed by the CPU. Further,
15 the aggregated log data would be recorded on a memory card by a card reader.

Log data unified to a predetermined format is furnished to the image provider even in a case where log data has been generated in a variety of prescribed
20 formats for each client terminal.

An arrangement may be adopted in which subsequent printing by a client terminal is allowed in dependence upon the printing conditions represented by the log data. For example, if printing has been performed more
25 than a fixed number of times by a client terminal, then printing by this client terminal would be allowed.

In the above-described embodiment, an offline client terminal reads image data that has been recorded

002260" TO 229360

on a CD-ROM, records log data on a floppy disk and applies the log data to the operations server 4.

However, an arrangement may be adopted in which the offline client terminal is provided with the

5 communication function of a modem or the like and the log data is transmitted to the operations server 4.

This is because the quantity of log data is less than that of image data and, hence, requires little time for transmission and can be transmitted efficiently.

10 As many apparently widely different embodiments of the present invention can be made without departing from the spirit and scope thereof, it is to be understood that the invention is not limited to the specific embodiments thereof except as defined in the appended
15 claims.

002260" T0449960

WHAT IS CLAIMED IS:

1. An image server for outputting encrypted image data to at least one client terminal among a plurality thereof, comprising:

5 a selection unit for selecting, from among the plurality of client terminals, a client terminal to which image data is to be output;

 an encryption unit for encrypting the image data using an encryption key which corresponds to the client
10 terminal that has been selected by said selection unit; and

 an encrypted image data output unit for outputting image data that has been encrypted by said encryption unit.

15 2. The image server according to claim 1, wherein the image data includes high-resolution image data for printing and display image data having a resolution lower than that of the high-resolution image data for printing; and

20 said encryption unit encrypting the high-resolution image data for printing.

3. A client terminal comprising:

 an input unit for inputting image data that has been encrypted using an encryption key which corresponds
25 to this client terminal;

 a decryption unit for decrypting encrypted image data, which has been input by said input unit, using the corresponding decryption key; and

002260" T049260

an output unit for outputting image data that has been decrypted by said decryption unit.

4. An image printing system comprising:

an image selection unit for selecting at least one
5 image from among a plurality thereof;

a print command unit for applying a command to print the image that has been selected by said image selection unit; and

a printing unit, which is responsive to a print
10 command applied by said print command unit, for printing, on the same visible recording medium, the image that has been selected by said image selection unit and information relating to a copyright holder of the selected image.

15 5. The system according to claim 4, further comprising an input unit for inputting data in which image data representing a plurality of images and information relating to copyrights of these images are associated with each other;

20 said image selection unit selecting a desired image from among the plurality of images represented by the image data input by said input unit.

6. An image printing system comprising:

a scanner for reading an image that has been
25 recorded on a visible recording medium and outputting image data representing the read image;

a determination unit for determining whether an image that has been read by said scanner contains

002260" 10/29/96

information relating to a copyright holder of the image;

an image printing unit for printing an image, which
has been read by said scanner, in accordance with a
determination by said determination unit that the read
5 image does not contain information relating to the
copyright holder; and

a printing controller for halting normal printing
of the image by said image printing unit in accordance
with a determination by said determination unit that the
10 read image contains information relating to the
copyright holder.

7. A data installing apparatus for reading data from a
first portable recording medium on which the data has
been recorded and installing the image data that has
15 been read, wherein a unique first password has been
stored in an image printing unit and said apparatus
comprises:

a password reading unit for reading a second
password from a second portable recording medium on
20 which the second password has been rewritably recorded;

a password determination unit for determining
whether the first password and the second password,
which has been read by said password reading unit,
match;

25 a first installation execution unit for executing
the installation in response to a determination by said
password determination unit that the first and second
passwords match; and

002260" T0449360

an installation inhibiting unit for inhibiting the installation in response to a determination by said password determination unit that the first and second passwords do not match.

- 5 8. The apparatus according to claim 7, wherein installation-count data indicating number installations has been recorded on the second portable recording medium, and said apparatus further comprises:

an installation-count reading unit for reading the
10 installation-count data indicating number installations recorded on the second portable recording medium;

a determination-halt unit for halting password determination by said password determination unit when number of installations represented by the installation-
15 count data read by said installation-count reading unit is zero;

a second installation execution unit for executing the installation in response to the halting of password determination by said determination-halt unit; and

20 an incrementing unit for incrementing the number of installations, which is represented by the data that has been recorded in said second portable recording medium, in response to execution of installation by said second installation execution unit.

- 25 9. The apparatus according to claim 8, wherein initial data is set as the second password when installation has not yet been performed;

said installation inhibiting unit inhibiting the

002260" FDZ 9950

installation in response to a number of installations that is zero and, moreover, a second password that is not initial data.

10. An image data output apparatus for outputting image
5 data corresponding to a plurality of image printing units which print images represented by image data, comprising:

a designation unit for designating an output destination of applied image data from among the
10 plurality of image printing units;

a format conversion unit for converting a format of the applied image data so as to obtain a format conforming to the image printing unit that has been designated by said designation unit; and

15 an image data output unit for outputting the image data, the format whereof has been converted by said format conversion unit, to the image printing unit that has been designated by said designation unit.

11. The apparatus according to claim 10, further
20 comprising an input unit for inputting an image file containing the image data and data indicating the output destination of this image data;

said designation unit designating the output destination of image data by data indicating the output
25 destination that is contained in the image file that has been input by said input unit.

12. A printing management apparatus for managing printing conditions in a plurality of image printing

002260" T0/29960

units which print images represented by image data,
wherein data representing printing history is output
from the image printing units and said apparatus
comprises:

- 5 a reading unit for reading data representing the
printing history output from the image printing units;
and

 a format conversion unit for converting the data
representing the printing history read by said reading
10 unit to data having a predetermined format.

13. The apparatus according to claim 12, further
comprising an aggregating unit for aggregating, for each
of the plurality of printing units, the data which
represents printing history and the format of which has
15 been converted by said format conversion unit.

14. A method of controlling an image server for
outputting encrypted image data to at least one client
terminal among a plurality thereof, said method
comprising the steps of:

- 20 selecting, from among the plurality of client
terminals, a client terminal to which image data is to
be output;

 encrypting the image data using an encryption key
which corresponds to the client terminal that has been
25 selected; and

 outputting image data that has been encrypted.

15. A method of controlling a client terminal,
comprising the steps of:

002250-1042950

inputting image data that has been encrypted using
an encryption key which corresponds to the client
terminal;

5 decrypting input encrypted image data using the
corresponding decryption key; and

outputting image data that has been decrypted.

16. An image printing method comprising the steps of:

selecting at least one image from among a plurality
thereof;

10 receiving a command to print the image that has
been selected;

in response to a print command applied by the print
command unit, printing, on the same visible recording
medium, the image that has been selected and information
15 relating to a copyright holder of the selected image.

17. An image printing method comprising the steps of:

reading an image that has been recorded on a
visible recording medium and acquiring image data
representing the read image;

20 determining whether an image that has been read
contains information relating to a copyright holder of
the image;

printing an image, which has been read, in
accordance with a determination that the read image does
25 not contain information relating to the copyright
holder; and

halting normal printing of the image in accordance
with a determination that the read image contains

002250-102250

20. A printing management method for managing printing
5 conditions in a plurality of image printing units which
print images represented by image data, wherein data
representing printing history is output from the image
printing units and said method comprises the steps of:

converting the data representing the printing history read to data having a predetermined format.

An image registration server stores encryption keys of respective ones of a plurality of client terminals. Image data is encrypted by the image registration server using the encryption key corresponding to the client terminal to which the image data is applied. The encrypted image data is applied to the client terminal via a server. The client terminal has a decryption key stored within so that only a client terminal that is duly authorized can decrypt encrypted image data. Other client terminals that are not duly authorized cannot decode the image data. This makes it possible to prevent unlawful use of image data even if the image data has been intercepted.





Fig. 2

Fig. 3





Fig. 4

CLIENT TERMINAL	KEY USED IN ENCRYPTION
NO. 1 ONLINE CLIENT TERMINAL	KEY A
NO. 2 ONLINE CLIENT TERMINAL	KEY B
⋮	⋮
NO. 1 OFFLINE CLIENT TERMINAL	KEY F
NO. 2 OFFLINE CLIENT TERMINAL	KEY G
⋮	⋮

Fig. 5






Fig. 7





Fig. 8


Fig. 9

Fig. 10a

BEFORE CONVERSION

<div>{ DATA FORMAT = Exif2.0 PRINT TARGET = NO. 1 ONLINE CLIENT TERMINAL PRINT SIZE = X DATA SIZE = 5000 Y DATA SIZE = 5000 COPYRIGHT HOLDER = JOHN SMITH }</div>	ENCIPHERED IMAGE DATA
---	-----------------------

ATTRIBUTE-INFORMATION
RECORDING AREA

IMAGE-DATA
RECORDING AREA

Fig. 10b


AFTER CONVERSION

<div>{ DATA FORMAT = Exif2.0 PRINT TARGET = NO. 1 ONLINE CLIENT TERMINAL PRINT SIZE = A4 X DATA SIZE = 2048 Y DATA SIZE = 3084 COPYRIGHT HOLDER = JOHN SMITH }</div>	ENCIPHERED IMAGE DATA
--	-----------------------

ATTRIBUTE-INFORMATION
RECORDING AREA

IMAGE-DATA
RECORDING AREA

Fig. 11



0966701.092200


Fig. 12



Fig. 13

Fig. 14



002260" T0229960


Fig. 15

Fig. 16

CLIENT TERMINAL
(SERIAL NO. ABC0001)

BEFORE INSTALLATION

```
{  
  NUMBER OF INSTALLATIONS = 0  
  INSTALLATION KEY = first time  
}
```

INSTALL



AFTER INSTALLATION

```
{  
  NUMBER OF INSTALLATIONS = 1  
  INSTALLATION KEY = ABC0001  
}
```


Fig. 17


Fig. 18

LOG DATA (TRANSMISSION)

TERMINAL ID : 0123ABC
IMAGE ID : 12110-00008-00000
SERVICE TIME : 8/9/1999; 18:54
PAPER TYPE : A6
NUMBER OF PRINTS : 2

Fig. 19

LOG DATA (FD)



002260-10229950


Fig. 20

Fig. 21

UNIFIED- FORMAT DATA

<PERSONAL INFORMATION>

<TERMINAL ID>

<IMAGE ID>

<SERVICE TIME>

<PAPER TYPE>

<NUMBER OF PRINTS>

002250"FDZ9950

Fig. 22

AGGREGATE LOG DATA

<PERSONAL INFORMATION>

<TERMINAL ID> 0123ABC <≠TERMINAL ID>

<IMAGE ID> 12110-00008-00000 <¥IMAGE ID>

<SERVICE TIME> 8/9/1999 18:54 <≠SERVICETIME>

<PAPER TYPE> A6 <≠PAPER TYPE>

<NUMBER OF PRINTS> 2 <≠NUMBER OF PRINTS>

<≠PERSONAL INFORMATION>

<PERSONAL INFORMATION 2>

<TERMINAL ID> 3210XYZ <≠TERMINAL ID>

<IMAGE ID> 13123-00017-00000 <¥IMAGE ID>

<SERVICE TIME> 8/13/1999 17:35 <≠SERVEICIE TIME>

<PAPER TYPE> SEAL <≠PAPER TYPE>

<NUMBER OF PRINTS> 3 <≠NUMBER OF PRINTS>

<≠PERSONAL INFORMATION 2>

DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

IMAGE SERVER AND METHOD OF CONTROLLING SAME

the specification of which:
(check one)

☐ (is attached hereto)
☐ was filed on _____,
as Application Serial No. _____
and was amended on _____. (if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, § 1.56*

I hereby claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)

			priority claimed	
JP11-271892	Japan	27/09/1999	X	
(Number)	(Country)	(Day/Month/Year Filed)	yes	no
_____	_____	_____	yes	no
(Number)	(Country)	(Day/Month/Year Filed)		
_____	_____	_____	yes	no
(Number)	(Country)	(Day/Month/Year Filed)		

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.)

(Filing Date)

(Status: patented, pending, abandoned)

Power of Attorney: As a named inventor, I hereby appoint Sean M. McGinn, Reg. No. 34, 386, and Frederick W. Gibb, III, Reg. No. 37,629, as attorneys and/or agents to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. All correspondence should be directed to McGinn & Gibb, P.C., 1701 Clarendon Boulevard, Suite 100, Arlington, Virginia 22209. Telephone calls should be directed to McGinn & Gibb, P.C. at (703) 294-6699.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole

Joint Inventor, If Any Yoshiki KAWAOKA

Inventor's Signature Yoshiki Kawaoka Date September 14, 2000

Residence Asaka-shi, Saitama, Japan

Citizenship Japanese

Post Office Address c/o FUJI PHOTO FILM CO., LTD.

11-46, Senzui 3-chome, Asaka-shi, Saitama 351-0024, Japan

Full Name of Second

Joint Inventor, If Any Norihisa HANEDA

Inventor's Signature Norihisa Haneda Date September 14, 2000

Residence Asaka-shi, Saitama, Japan

Citizenship Japanese

Post Office Address c/o FUJI PHOTO FILM CO., LTD.

11-46, Senzui 3-chome, Asaka-shi, Saitama 351-0024, Japan

Full Name of Third

Joint Inventor, If Any Hiroshi SUGANUMA

Inventor's Signature Hiroshi Suganuma Date September 14, 2000

Residence Asaka-shi, Saitama, Japan

Citizenship Japanese

Post Office Address c/o FUJI PHOTO FILM CO., LTD.

11-46, Senzui 3-chome, Asaka-shi, Saitama 351-0024, Japan

Full Name of Fourth

Joint Inventor, If Any Hiroyuki YOSHINAGA

Inventor's Signature Hiroyuki Yoshinaga Date September 14, 2000

Residence Asaka-shi, Saitama, Japan

Citizenship Japanese

Post Office Address c/o FUJI PHOTO FILM CO., LTD.

11-46, Senzui 3-chome, Asaka-shi, Saitama 351-0024, Japan

(An additional sheet(s) is/are attached hereto if the present invention includes more than four inventors.)

*Title 37, Code of Federal Regulations, § 1.56:

(a) A patent by its very nature is affected with a public interest. The public interest is best served, and the most effective patent examination occurs when, at the time an application is being examined, the Office is aware of and evaluates the teachings of all information material to patentability. Each individual associated with the filing and prosecution of a patent application has a duty of candor and good faith toward the Patent and Trademark Office, which includes a duty to disclose to the Office all information known to that individual to be material to patentability as defined in this section. The duty to disclose information exists with respect to each pending claim until the claim is canceled or withdrawn from consideration, or the application becomes abandoned.

(b) Under this section, information is material to patentability when it is not cumulative to information already of record or being made of record in the application, and (1) it establishes by itself or in combination with other information, a prima facie case of unpatentability; or (2) it refutes, or is inconsistent with, a position the applicant takes in: (i) opposing an argument of unpatentability relied on by the Office, or (ii) asserting an argument of patentability.